



8	7	6	5	4	3	2	1
				REV.	DESCRIPTION	DATE	DESIGN

P1

P2

Electrical character:
 a. 100% open & short testing;
 b. Withstanding voltage: DC 300V 0.01Sec;
 c. Insulation resistance: 5M Ohm (Min);
 d. Conductive resistance 3 Ohm (Max).
 e. Support 10Gbps transmission speed

P1-AM		P2 TYPE-C	
VBUS	1	VBUS	B5
D-	2	D-	A5
D+	3	D+	A7
GND	4	GND	A6
RX1-	5	GND	A1-B1-A12-B12
RX1+	6	TX1-	A3
GND	7	TX1+	A2
TX1-	8	GND	A1-B1-A12-B12
TX1+	9	RX1-	B10
GND	SHELL	RX1+	B11
		GND	SHELL

Client	KM1262	KM1263
Length	500±20mm	1000±30mm

- JACK: 4.5mm PVC
- BRAID: 96#/0.08TC
- AL/MY
- INSULATION
- CONDUCT: 7/0.10TC
- DRAIN: D7/0.10BC
- FILLER

CABLE SPECIFICATION

⑦	OUTER MOLDED	Black PVC		
⑥	INNER MOLDED	LDPE		
⑤	SHELL	Type CM AL Shell, Grey, 11.35*6.63*17	PCS	1
④	SHELL	USB AM AL Shell, Grey, 18*14*6.5mm,	PCS	1
③	CON	Type CM, Nickel Plated	PCS	1
②	CON	USB AM, Nickel Plated	PCS	1
①	CABLE	[(7/0.10TC+FPE0.7)*1P+7/0.1TC+AL+MY]*1P+(7/0.10TC+HDPE0.52)*1P+(41/0.10TC+PP0.88)*2C+AL+MY+D7/0.10BC+96#/0.08TC+OD:4.5mm Black	PCS	1
NO.	ITEM	DESCRIPTION	UNIT	Q'TY

X.±0.20		Drawing No. JXD-UC1107/NI/BK			
.X±0.15					
.XX±0.10					
REV	A/0	Title	USB 3.0 AM-Type C M	Draw	Song
Scale	/	Customer	JXDSZ-036	Checked	
Page	1/1	Item No.	-	Sales	
Unit	mm	Date	2023/03/30	Approval	